

Dome D100/M410



Specifications

· ADVANCED HIGH RESOLUTION COLOR DOME CAMERA W/BUILT-IN IR LED

MODEL NO	D100IR/M410
CCD TYPE	1/3" COLOR SONY SUPER HAD CCD
PIXELS	410K
RESOLUTION	520TV-LINE (SONY HQ1)
SYNC.TYPE	Internal
SCANNING	2:1 Interlace
VIDEO OUTPUT	1.0Vp-p (Sync. Negative)
r (Gamma)	r=0.45 typ
WHITE BALANCE	ATW
BLC	ON/OFF(Selectable-option*)
MIRROR	OFF(ON-option*)
FLICKERLESS	OFF(ON-option*)
AGC	Normal(High-option*)
Lens Mount	Fixed focal Board Lens 3.6mm
MIN.ILLUMINATION	0 Lux (20M Range): LED ON

	0.5Lux (F/1.2): LED OFF
S/N RATIO	45dB or More(AGC OFF)
Gain Control	Automatic
SHUTTER SPEED	Auto: 1/60 ~ 1/100,000 sec Flickerless OFF: 1/60(50)sec, ON:1/100(1/120)sec
POWER SUPPLY	Regulated DC 12.0V
CURRENT CONSUMPTION	Max. 380mA(LED ON)
Audio Gain(option)	40dB \pm 10%
Max Output(option)	600ohm Max 3Vpp \pm 10%
Freq. Respones(option)	300Hz ~ 20KHz
Audio S/N Ration(option)	-45dB \pm 10%
OPERATION TEMP.	-10°C~+50°C
PRESERVATION TEMP.	-20°C~+60°C
ACCESSORY BRACKET	SK-AB01