

# SE-TE668P

## Image



## Application



## Functions

### Video Tester

CCTV video field monitor, 2.5" LCD monitor. With brightness, contrast, chroma adjustable.

### PTZ Controller

With Pelco-D, Pelco-P, Vicon, VCL, Samsung, Panasonic, Kalatel, Dynacolor etc. protocols selectable via OSD menu, strong compatibility with most of the PTZ cameras. Pelco-Coaxitron added, make the testing easier for connecting only video cable to transmit both video and data signal.

### PTZ Command Analyzer

Receive PTZ code from keyboard (DVR) so that user can analyze the PTZ command.

### Network Cable Tester

With a RJ45 testing terminal (equipped in the package), can test the network cable status, LED display and wrong information display on the screen for 8 pins connection.











### RS485 Polarity Tester

Can test the RS485 data cable polarity, display on the LCD screen with + or -.

### Power Supplier to Camera (New)

Can provide 12VDC Max.300mA power to camera Features

## Feature:

-  2.5" LCD monitor. With brightness, contrast, chroma adjustable.
-  PAL/NTSC auto adaptable
-  Pocket size, easy and convenient operation
-  With a LCD cover, can protect the LCD monitor from scratches when putting into the
-  2 piece 18490 Li Battery-powered or DC12V/2A power
-  With audio input and built-in speaker
-  With sleep function, can set the unit switch off automatically after a period of time without
-  With Macro buttons for user to set the macro function according to his specific request on
-  OSD menu On/off selectable to avoid overlap with the
-  With mounting stand and standard camera mounting screws, easy for hands free operation when putting

## Package Includes

1	CCTV Tester
2	UTP test terminal
3	2pcs Rechargeable Li Battery
4	DC12V 2A Power adapter
5	Video cable 1M
6	Necklace
7	User Manual



## General Information

Work Temperature	-30oC---+ 70oC
Work Humidity	30%-90%
Dimension	170mm x 90mm x 45mm
Inner box	22.5 21.5 8.5cm
Package	10pcs /carton, 44 26.5 42cm, 7.8kg

