

Features:

- ◆ 2.5" IP66 Vandalproof Medium Speed IR Dome PTZ
- ◆ Support TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
- ◆ Support Onvif, Preset: 255
- ◆ lightning-proof, surge-proof, External PoE Optional(add \$6)
- ◆ 3pcs IR Array Led, IR Range: 30M
- ◆ Pan Range: 355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec
- ◆ Video Compression: H.264 Main Profile, MJPEG/JPEG Baseline
- ◆ Built-in Temperature Control
- ◆ Size: 103mm x 98mm(H)
- ◆ Weight: 1KG



Specification:

Description	2.5" IP66 Vandalproof Medium Speed IR Dome PTZ,3pcs IR Array Led, IR Range: 30M	
TV System	NTSC / PAL	
Image Sensor	1/3" CMOS 2.0 Mega	1/3" CMOS Sensor 2.0 Mega
Resolution	1/3" 2.0 Mega Pixels CMOS HI3516E+SONY307 Starlight Low Illumination	1/3" 5.0 Mega Pixels CMOS HI3516D+5521 Low Illumination
Effective Pixels	1920(H) × 1080(V)	2592(H)×1944(V)
Lens	4x Optical Zoom(2.8-12mm Lens)	
Minimum illumination	0.01Lux @(F1.6,AGC ON) ,0 Lux with IR	
Video interface	BNC	
Video compression	H.264	
Signal model	60HZ:30fps	
Video bit rate	32kbps-16Mbps	
Day and night conversion	IR-Cut	
Electronic shutter	1/25s ~ 1/100000s	
D-WDR	Support	
DNR	2D/3D-DNR	
Mirror	YES	
BLC	YES	
MD	YES	
POE	Optional	
Onvif	YES	
Pan Range	0—350°	
Tilt Range	0—90°	
Horizontal speed	Max 30°/ s	
Vertical speed	Max 30°/ s	
Preset	255	
Audio I/O	Optional	
Audio compression	G.711A	
Alarm I/O	Optional	
Waterproof level	IP66	
Size	103mm x 98mm(H)	
Weight	1.0 kg	
Power	DC12V/2A	
Work temperature	-30℃~60℃	